



Mahatma Gandhi Antarrashtriya Hindi Vishwavidyalaya, Wardha

Gandhi Hill, Wardha- 442001. (Maharashtra) [Phone No. 07152 – 232669] [Website : www.hindivishwa.org]

Tender No. MGAHV/CD/34/2022-23/05

Date: 21 / 06/2022

Tender Notice

Sealed tenders are invited for Construction of 02 Nos. Parking Shed in Saket Sankul at MGAHV, Wardha. The tender should reach the University on or before | | /07/2022 up to 04:00 p.m.

The detailed terms and conditions of tender can be obtained from www.hindivishwa.org and www.eprocure.gov.in

Registrar

21/18/11





MAHATMA GANDHI ANTARRASHTRIYA HINDI VISHWAVIDYALAYA

Post Hindi Vishwavidyalaya, Gandhi Hills, Wardha-442 001.

(Phone 07152-232669 Fax No 07152-247602) [Website: www.hindivishwa.org]

Tender No.: MGAHV/CD/34/2022-23/05

Date: 21.06.2022

TENDER FOR Civil & Fabrication work

TENDER FORM SALE WILL START FROM

10.00 AM on 21.06.2022

LAST DATE FOR SALE OF TENDER FORM

Upto 03.00 PM on 10.07.2022

LAST DATE FOR SUBMISSION OF TENDER FORM

Upto 4.00 PM on 11.07.2022

DATE OF OPENING OF TENDER (i.e. Technical Bid)

At 05.00 PM on 11.07.2022

Tender available on www.eprocure.gov.in & www.hindivishwa.org

TENDER FORM PRICE Rs. 500/-



महात्मा गांधी अंतरराष्ट्रीय हिंदी विश्वविद्यालय, वर्धा

(संसद द्वारा पारित अधिनियम के अन्तर्गत स्थापित केन्द्रीय विश्वविद्यालय) पोस्ट-हिंदी विश्वविद्यालय, गांधी हिल्स, वर्धा - 442001 (महाराष्ट्र), (फोन-07152-232669 फैक्स-07152-247602)

वेबसाइट :www.hindivishwa.org

Name of work:

Construction of 02 Nos. Parking Shed in Saket Sankul at MGAHV,

Wardha.

Tender No.: MGAHV/CD/34/2022-23/ Q.S..

Date: 21.06.2022

(Technical Bid and other conditions)

1 - कार्य का विवरण

- संलग्न

2- EMD राशि रु. 49000/-

मांगपत्र- वित्ताधिकारी म.गां.अं.हिं.वि..वर्घा. महाराष्ट्र के नाम देय

- 3. जी.एस.टी. क्रमांक अनिवार्य। (छायाप्रति संलग्न करना अनिवार्य)
- 4. PAN क्रमांक अनिवार्य। (छायाप्रति संलग्न करना अनिवार्य)
- 5. विगत क्रमिक तीन वर्षों का केन्द्र सरकार एवं राज्य सरकार के अनुदानित संस्थानों में सिविल एवं फैब्रिकेशन कार्य कराने का अनुभव प्रमाण पत्र जमा करना अनिवार्य होगा। जो कि प्रत्येक वित्तीय वर्ष में रूपया पचास लाख से कम न हो।
- 6. Technical & Financial bid को अलग-अलग लिफाफों में सीलबंद कर एक बड़े लिफाफे में डालकर लिफाफा बंद करना होगा और उस लिफाफे पर 'Construction of 02 Nos. Parking Shed in Saket Sankul at MGAHV, Wardha.' लिखकर जमा करना अनिवार्य होगा।
- 7. निविदा भरने से पूर्व कार्यस्थल का निरीक्षण करना अपेक्षित है। किसी भी प्रकार की जानकारी/स्पष्टीकरण परिसर विकास विभाग कार्यालय से कार्य दिवसों/कार्य समयों में प्राप्त की जा सकती है।
- 8. निविदा में दी गई दरें 06 (छः) माह तक वैध रहेंगी।
- 9. कायदिश जारी होने के पश्चात 60 दिनों में कार्य पूर्ण करना होगा।
- १०.उक्त निविदा में संपूर्ण सामग्री, श्रमिक व्यय एवं कर आदि सम्मिलित करना होगा।
- 11. निविदाकारक को विगत क्रमिक तीन वर्षों का आयकर रिटर्न प्रमाण पत्र जमा करना अनिवार्य होगा।
- 12.श्रमिकों का बीमा होना अनिवार्य। (कायदिश प्राप्ति के बाद परिसर विकास विभाग में प्रमाण पत्र प्रस्तुत करने के बाद ही कार्य प्रारम्भ करना होगा)
- 13. कोरोना वायरस के फैलाव को रोकने हेतु सामाजिक दूरी (Social Distance) बनाए रखने एवं सरकारी दिशानिर्देशों का पालन करते हुए निविदाकारक एवं श्रमिकों द्वारा कार्य का निष्पादन किया जाएगा।

Page 3 of 12

- 14. कार्य के दौरान यदि किसी प्रकार की दुर्घटना घटित होती है तो उसकी संपूर्ण जिम्मेदारी निविदाकारक की होगी।
- 15. कायदिश प्राप्त निविदाकर्ता को भारत सरकार/महाराष्ट्र सरकार के श्रम कानूनों, बाल मजदूरी कानूनों आदि नियमों का पालन करना अनिवार्य होगा।
- 16. कार्यादेश प्राप्त निविदाकर्ता को कार्यों की गुणवत्ता सुनिश्चित करने संबंधी केंद्रीय लोक निर्माण विभाग की विशिष्टियों के अनुरूप कार्य सम्पादित करना होगा तथा बिल के साथ आवश्यक टेस्ट रिपोर्ट जमा किया जाना होगा।
- 17. कार्य के दौरान होने वाली किसी भी प्रकार की क्षित के लिए विश्वविद्यालय का उत्तरदायित्व अथवा देनदारी नहीं होगी और न ही इस प्रकार का कोई दावा न तो कायदिश प्राप्त निविदाकर्ता द्वारा और न श्रीमकों द्वारा किया जायेगा और न ही विश्वविद्यालय द्वारा स्वीकार किया जायेगा।
- 18. वित्तीय निविदा में विभिन्न आइटमों की दर्शायी गयी मात्रा अनुमानित है। कार्य सम्पादन के समय किसी भी आइटम की मात्रा में संशोधन हो सकता है या कोई कार्य नहीं भी सम्पादित कराये जाने का निर्णय लिया जा सकता है। उक्त हेतु कायदिश प्राप्त निविदाकर्ता का कोई दावा स्वीकार नहीं होगा।
- 19. कार्य के दौरान यदि विश्वविद्यालय की बिजली का उपयोग किया जाता है तो प्रति यूनिट रु. 10.00 के अनुसार कायदिश प्राप्त निविदाकर्ता को विश्वविद्यालय के पक्ष में भुगतान करना होगा। कायदिश प्राप्त निविदाकर्ता द्वारा बिजली मीटर का व्यय स्वयं वहन करना होगा तथा विभाग के इलेक्ट्रीशियन के माध्यम से ही बिजली कनेक्शन लेना होगा।
- 20. निविदा प्रपत्र एवं संलग्न दस्तावेज के प्रत्येक पृष्ठ पर निविदाकारक द्वारा हस्ताक्षर एवं मुहर लगाना अनिवार्य है।
- 21. वित्तीय निविदा में दरों का अधिलेखन (Overwriting) मान्य नहीं होगा इसलिए वित्तीय निविदा में दरों को बहुत ही ध्यान से और बिना अधिलेखन (Overwriting) के भरा जाए।
- 22. वित्तीय निविदा में त्रुटिपूर्ण गणना (Wrong Calculation) मान्य नहीं होंगी। किसी भी प्रकार के संदेह की स्थिति में शब्दों में लिखी गई राशि ही मान्य होगी।
- 23. निविदा को कुलसचिव कार्यालय में रखे Tender Box में डालना होगा।
- 24. सभी अर्हताएँ निविदा जमा करने से पूर्व या अंतिम तिथि तक पूर्ण करना अनिवार्य है।
- 25. निविदा प्रपत्र प्राप्त करने हेतु 'वित्ताधिकारी, म.गां.अं.हिं.वि., वर्धा (महाराष्ट्र)' के नाम से देय रू. 500/– (रू. पांच सौ मात्र) का डिमांड ड्राप्ट परिसर विकास विभाग में जमा कर निविदा प्रपत्र प्राप्त किया जा सकता है। यदि निविदाकारक द्वारा वेबसाइट से निविदा प्रपत्र डाउनलोड कर निविदा जमा की जाती है तो उक्त निविदा प्रपत्र के साथ 'वित्ताधिकारी, म.गां.अं.हिं.वि., वर्धा (महाराष्ट्र)' के नाम से देय रू. 500/– का डिमांड ड्राप्ट जोड़ना अनिवार्य है।
- 26. निविदा प्राप्त करने वाली फर्म को कायदिश जारी होने के 05 दिनों के अंदर निविदा की लागत का 05% Performance Security के रूप में 06 माह के लिए धनराशि डी.डी. के माध्यम से 'वित्ताधिकारी, म.गां. अं.हिं.वि., वर्षा (महाराष्ट्र)' के नाम से विश्वविद्यालय में जमा करना अनिवार्य होगा।

- 27. तकनीकी निविदा में सफल निविदाकारक को ई-मेल/दूरभाष के माध्यम से सूचित किया जाएगा जिससे तकनीकी निविदा में सफल समस्त निविदाकारक 'वित्तीय निविदा' खुलने के समय उपस्थित रह सकें। अतः लिफाफे के ऊपर ईमेल, मोबाइल नम्बर एवं पता अवश्य लिखें।
- 28. निविदा में किसी भी प्रकार के परिवर्तन/सुधार/संशोधन होने पर उक्त की सूचना मात्र विश्वविद्यालय की वेबसाइट www.hindivishwa.org पर प्रकाशित की जाएगी इसलिए वेबसाइट लगातार देखते रहें।
- 29. विश्वविद्यालय के पास किसी भी स्तर पर निविदा में निर्धारित जानकारी, शर्तों, प्रक्रिया और प्रोटोकॉल को रद्द करने और जोड़ने का विवेकाधिकार सुरक्षित होगा। इसके खिलाफ निविदाकर्ता का कोई भी दावा स्वीकार्य नहीं होगा।
- 30. विश्वविद्यालय बिना कोई कारण बताये किसी भी समय निविदा को निरस्त करने का अधिकार अपने पास सुरक्षित रखता है। किसी भी विवाद की दशा में विवादों का क्षेत्राधिकार वर्धा (महाराष्ट्र) ही होगा।

टेंडर भरने वाले का हस्ताक्षर एवं मुहर

(Financial Bid)

Name of work: Construction of 02 Nos. Parking Shed in Saket Sankul at MGAHV, Wardha. Date: 21 .06.2022

Tender No. MGAHV/CD/34/2022-23/95...

(Part-A)

l _c	.н.н. с. е. н	A	2 E (1) the contract of the co	A	a t n (C)	0	No.	
	Excavation work by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drains (not exceeding 1.5m in width or 10 sq m on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directed, within a lead of 50 m	All kinds of soil	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sq m on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m	All kinds of soil	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5 m in width as well as 10 sq m on plan) including disposal of excavated earth, lead up to 50m and lift up to 1.5m, disposed earth to be leveled and neatly dressed.	Civil Work	Description	
19 85		19.85		172.67			Quantity	
Cu. m		Cu. m		Cu .m	-		Unit	
							Rate	
							Total Amount (In figure)	
							Total Amount (In words)	

S. Description Quantity Unit Rate Total Amount Total Amount Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering. All work up to plinth level 140 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-22 grade cement concrete for reinforced cement concrete work, using cement concrete vork, using cement concrete vork, using cement concrete vork, using coment concrete vork using coment concrete work using coment concrete work using coment concrete work using coment concrete work using coment concrete vork using coment vork using vork using coment vork using vork u				Sqm	6.93	1:4 (1 cement: 4 coarse sand)	
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering -All work up to plinth level 1:4.8 (I Cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix, M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per 15: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc. and removal of form for: Foundations, footings, bases of columns, etc. for mass concrete Columns, Pillars, Piers, Abutments, Posts and Struts Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete up to plinth level. Thermo-Mechanically Treated bars Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering in position cement concrete of specified grade excluding the cost of centering and complete up to plinth level. Providing and laying in position cement concrete of specified grade excluding the cost of centering and complete appropriate the cost of centering and complete appropriate the cost of centering and complete excluding the cost of centering and complete appropriate the cost of centering and complete appropriate cost of centering and complete appropriate cost of centering and complete appropriate cost of centering and cost of centering and complete appropriate cost of centering and cost of centering cost of centering and cost of centering cost of centering cost o						20 mm cement plaster of mix:	9
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate				Cum	64.23	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering. All work up to plinth level 1.4.8 (1 Cement: 4 coarse sand: 8 graded stone aggregate 46.05 Cu. m 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix including pumping of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc. Foundations, footings, bases of columns, etc. for mass Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete up to plinth level. Steel reinforcement for R.C.C. work including straightening cutting, bending, placing in position and binding all complete up to plinth level. 850.00 Kg.						and laying in position cement concrete grade excluding the cost of centering a All work up to plinth level	∞
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering -All work up to plinth level 1.4:8 (1 Cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc. and removal of form for: Foundations, footings, bases of columns, etc. for mass Columns, Pillars, Piers, Abutments, Posts and Struts Steel reinforcement for R.C.C. work including strutting all complete up to plinth level.				Kg.	850.00	Thermo-Mechanically Treated bars	
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1.4.8 (1 Cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement concrete to site of laying but excluding pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS. 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc. and removal of form for: Foundations, footings, bases of columns, etc. for mass 25.20 Sqm Columns, Pillars, Piers, Abutments, Posts and Struts 25.20 Sqm						reinforcement for R.C.C. work htening, cutting, bending, placing in pogall complete up to plinth level.	7
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc. and removal of form for : Foundations, footings, bases of columns, etc. for mass 35.19 Quantity Unit Rate (In figure) (In figure) (In figure) (In figure) (In figure)				Sqm	25.20	Columns, Pillars, Piers, Abutments, Posts and Struts	
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement concrete to site of laying but excluding pumping of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Centering and shuttering including strutting, propping etc.				Sqm	35.19		
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement concrete to site of laying but excluding pumping of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. All works up to plinth level Rate Total Amount (In figure) (In figure) Cu. m Cu. m Cu. m All works up to plinth level Cu. m Sement concrete work, using cement concrete work, using cement concrete work, using cement concrete to site of laying but excluding pumping of concrete in cost of centering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge.	ess ()					Centering and shuttering including strutting, propping etc. and removal of form for :	6
Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement concrete to site of laying but excluding pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge.				Cum	8.32	All works up to plinth level	
Description Quantity Unit Rate Total Amount (In figure)				Си. т	66.05	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:4:8 (1 Cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge.	۸ 4
	Total Amount (In words)	Total Amount (In figure)	Rate	Unit	Quantity	Description	No.

	=				
13		12	1	10	No.
Providing and fixing percolated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sq m as per IS: 277, in 240 m pa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length up to 12 metre or as desired by Engineering-charge. The sheet shall be fixed using self drilling / self tapping screws of size (5.5x 55 mm) with EPDM seal, complete up to any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purling, rafters and trusses and including cutting to size	rior ministed werden type tubes	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete	Providing and fixing on wall face un plasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socked pipes.	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift up to 1.5 m	Description
219.20	2032.43	2632 43	15.00	39.69	Quantity
Sq.m	78.	K ₀	Rmt	Cum	Unit
					Rate
					Total Amount (In figure)
					Total Amount (In words)

					TOTAL (A)	
			Cum	23.08	In cement mortar	
					Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.	17
			Sqm	194.00	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer-in-charge.	16
			Sqm	109.60	Two or more coats on new work	
					Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:	15
			Rmt	27.40	Ridges plain (500 - 600mm)	
					Providing and fixing percolated galvanized steel sheet roofing accessories 0.50 mm (+ 0.05 %) total coated thickness, Zinc coating 120 grams per sq m as per IS: 277, in 240 m pa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete:	14
Total Amount (In words)	Total Amount (In figure)	Rate	Unit	Quantity	Description	No.

(Part-B)

Sec.	→	4 Pr m re si si si sh ac ac E.	4(3 Pr sp sh	A	2 Ea ex (in in dididididididididididididididididi	Α	1 E de di 1.	No.	S	
Centering and shuttering including strutting, propping etc.	All works up to plinth level	Providing and laying in position machine batched and machine mixed design mix M-25 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping of concrete to site of laying but excluding the cost of centering, shuttering, finishing and reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge	1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:	All kinds of soil	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m	All kinds of soil	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed.	A company	Description	
	5.94		33.76		28.35		63.45		ζ	Ouantity	Ī
	Cum		Cum		Cum		Cum	×		Unit	
(3)										Rate	
									(In figure)	Total Amount	
									(In words)	Total Amount	

Page 10 of 12

	12		=	9		8		7		6				No.
Hot finished welded type tubes	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete	110 mm diameter	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m	1:4 (1 cement: 4 coarse sand	20 mm cement plaster of mix:	1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:	Thermo-Mechanically Treated bars	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete up to plinth level.	Columns, Pillars, Piers, Abutments, Posts and Struts	Foundations, footings, bases of columns, etc. for mass concrete	form for :	Description
1703.94		10.00		28.35	4.95		31.73		600.00		18.00	27.90		Quantity
Kg		Rmt		Cum	Sq m		Cum		Kg		Sqm	Sqm		Unit
														Rate
														Total Amount (In figure)
														Total Amount (In words)

				Two o	1 5 Paintii manuf	Ridge	roofin thickn in 240 side o	sheets Engine thickn 277, ii both s: Sheet minim should desiree using mm) horizo purlin:	No.
GRAND TOTAL	GST @	TOTAL (A+B)	TOTAL (B)	Two or more coats on new work	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:	Ridges plain (500 - 600mm	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+ 0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete:	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineerin-charge. The sheet shall be fixed using self drilling / self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required	Description
				99.75		27.40		199.50	Quantity
				Sq.m.		Rmt		Sqm	Unit
									Rate
									Total Amount (In figure)
									Total Amount (In words)

टेंडर भरने वाले का हस्ताक्षर एवं मुहर Page 12 of 12

